

Product Data Sheet Application: External Walls

ISOVER CAVITY WALL SLAB (CWS) 36



Thermal Insulation for External Masonry Cavity Walls

Isover Cavity Wall Slab (CWS) 36 is a glass mineral wool slab providing thermal performance in external masonry cavity walls. Manufactured with a water repellent binder, the strong, resilient and flexible slabs are 455mm wide to fit between standard wall tie spacing.

Features and Benefits



Thermal Performance

Thermal conductivity of 0.036 W/m.K. Helps to reduce heat loss within the building envelope and decrease energy costs.



BBA Certified

Cavity Wall Slab (CWS) 36 has been assessed by the BBA as fit for use in defined full fill and partial fill masonry cavity wall applications if installed, used and maintained as set out in the certificate. Please read the certification at isover.co.uk/BBA for full details and restrictions.



Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.



Sustainability

Manufactured from up to 82% recycled glass on a plant that uses 100% renewable electricity. For further details, see the Environmental section below or visit isover.co.uk/CSR



Easy to Install

Slabs are 455mm wide to fit standard wall tie spacing for straightforward installation. No requirement for retaining discs when fully filling the cavity.

Key Considerations

When using Isover Cavity Wall Slab (CWS) 36, you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Please refer to the following product documents which are available at isover.co.uk/products/isover-cavity-wall-slab-cws-36 (product properties) and isover.co.uk/healthandsafety (safety properties):

- BBA certificate
- Declaration of Performance
- Safe Use Instruction Sheet

λD Declared **RD** Declared Slabs per Pack area Pallet area Packs per thermal thermal Product code Thickness (mm) Length (mm) Width (mm) pallet conductivity resistance pack (m²) (m²) (W/m.K) (m².K/W) 5200625441 455 218.40 0.036 1.35 50 1200 20 10.92 20 65 16 1.80 5200625443 1200 455 8.74 25 218.40 0.036 5200625445 75 1200 455 16 8.74 20 174.72 0.036 2.05 5200625447 85 1200 455 12 6.55 20 131.04 0.036 2.35 5200625449 100 1200 455 12 6.55 20 131.04 0.036 2.75 5200625451 125 1200 455 8 4.37 25 109.20 0.036 3.45 5200625453 150 1200 455 3.28 20 65.52 0.036 4.15 6

Product Specification

Characteristics

Thermal Fire Environmental	Declared thermal conductivity of 0.036 W/m.K under EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products. Euroclass A1 Reaction to Fire classification according to EN 13501-1. All Isover products are manufactured under Environmental Management System – ISO 14001:2015.	Certification	UKCA Marked to BS EN 13162. CE Marked to EN 13162. Designation code: MW-EN 13162-T4-WS. BBA Approved (Cert No: 18/5560) for full fill and partial fill masonry cavity wall applications when installed, used and maintained as set out in the certification. Please visit isover.co.uk/BBA to read the full certification for details and restrictions.
Recycled Content	Manufactured from up to 82% recycled glass.	Handling, Storage, Health and Safety	Information regarding storage, installation and handling of Isover products and health & safety information can be found at isover.co.uk/healthandsafety.
		Quality	All Isover products are manufactured under Quality

All Isover products are manufactured under Quality Management Standard - ISO 9001



Isover

Saint-Gobain Isover UK Limited, Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.

Customer Service -Order Placement and Enquiries Tel: 0800 0322 555 Email: isover.customerservice@saint-gobain.com

Technical Support Team

isover.co.uk

Isover reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at isover.co.uk

Saint-Gobain Isover UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.