

Product Data Sheet

Application: Multi-purpose

MODULAR ROLL



Multi-purpose Thermal Insulation

Modular Roll is a glass mineral wool insulation that can be considered for covering large areas in buildings. It is supplied in 1200mm wide un-split rolls for quick coverage.

Features and Benefits



Thermal Performance

Thermal conductivity of 0.043 W/m.K.
Helps to reduce heat loss within the building envelope and decrease energy costs.



Sustainability

Manufactured from up to 82% recycled glass on a plant that uses 100% renewable electricity. For further details, see the Environmental section below or visit insulation-uk.com/CSR



Fire Classification

Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.



Easy to Install

1200mm wide un-split rolls help to provide quick coverage of large areas.

Key Considerations

When using ISOVER Modular Roll, you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Please refer to the following product documents:

- Declaration of Performance - available at insulation-uk.com/dop
- Safe Use Instruction Sheet - available at insulation-uk.com/healthandsafety

Product Specification

Product code	Thickness (mm)	Length (m)	Width (m)	Roll area (m ²)	Rolls per pallet	Pallet area (m ²)	λD Declared thermal conductivity (W/m.K)	RD Declared thermal resistance (m ² .K/W)
5200625416	60	15.50	1.20	18.60	24	446.40	0.043	1.35
5200625351	80	11.25	1.20	13.50	24	324.00	0.043	1.85
5200625353	100	9.17	1.20	11.00	24	264.10	0.043	2.30

Characteristics

Thermal Declared thermal conductivity of 0.043 W/m.K under EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.

Fire Euroclass A1 Reaction to Fire classification according to EN 13501-1.

Environmental All Isover products are manufactured under Environmental Management System - ISO 14001:2015.

Recycled Content Manufactured from up to 82% recycled glass.

Certification UKCA Marked to BS EN 13162.
CE marked to EN 13162.
Designation code: MW-EN 13162-T1.

Handling, Storage, Health and Safety Information regarding storage, installation and handling of ISOVER products and health & safety information can be found at insulation-uk.com/healthandsafety. Achieves a Eurofins Gold product status for indoor air quality (certificate available at insulation-uk.com/Eurofins). EUCEB certified, demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008 (to download the certification, please visit insulation-uk.com/accreditations.)

Quality All ISOVER products are manufactured under Quality Management Standard - ISO 9001.



ISOVER

White House Industrial Estate,
Runcorn, Cheshire, WA7 3DP

**Customer Service -
Order Placement and Enquiries**

Tel: 01473 820820

Email: iukcustomerservice@saint-gobain.com

Technical Support Team

Email: isover.technical@saint-gobain.com

insulation-uk.com

Published date: 29 Feb 2024

ISOVER reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at insulation-uk.com

Saint-Gobain ISOVER UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.