

Product Data Sheet

Application: External Walls

ISOVER TIMBER FRAME BATT 35



Thermal Insulation for Timber Frame Walls

Isover Timber Frame Batt 35 is a glass mineral wool batt that can be used in timber frame walls. The resilient and flexible batts can be friction fitted between standard timber studs, ensuring straightforward installation and helping to minimise gaps and therefore maximise thermal performance.

Features and Benefits



Thermal Performance

Thermal conductivity of 0.035 W/m.K. Helps to reduce heat loss within the building envelope and as a result decreases energy costs.



Acoustic Benefits

The fibre structure of the glass mineral wool traps sound energy, helping to improve the acoustic comfort of those living or working within the building.



Sustainability

Manufactured from up to 82% recycled glass with all electric equipment in the plant powered by 100% renewable electricity. For further details visit [isover.co.uk/CSR](https://www.isover.co.uk/CSR)



Fire Classification

Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.



Ease of Install

Straightforward to handle, cut and install with minimal waste (off-cuts can be reused). Friction fits between 600mm timber stud centres with no need for additional fixings.

Key Considerations

When using Isover Timber Frame Batt 35, you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Please refer to the following product documents which are available at isover.co.uk/products/isover-timber-frame-batt-35 (product properties) and isover.co.uk/healthandsafety (safety properties):

- Declaration of Performance
- Safe Use Instruction Sheet

Product Specification

Product code	Thickness (mm)	Length (mm)	Width (mm)	Batts per pack	Pack area (m ²)	Packs per pallet	Pallet area (m ²)	AD Declared thermal conductivity (W/m.K)	RD Declared thermal resistance (m ² .K/W)
5200625414	90	1175	570	10	6.70	16	107.16	0.035	2.55
5200625335	100	1175	570	8	5.36	16	85.73	0.035	2.85
5200625388	140	1175	570	6	4.02	16	64.30	0.035	4.00
5200625333	150	1175	570	6	4.02	16	64.30	0.035	4.25

Characteristics

Thermal	Declared thermal conductivity of 0.035 W/m.K under EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.
Fire	Euroclass A1 Reaction to Fire classification according to EN 13501-1.
Environmental	All Isover products are manufactured under Environmental Management System - ISO 14001:2015.
Recycled Content	Manufactured from up to 82% recycled glass.
Certification	UKCA Marked to BS EN 13162. CE marked to EN 13162. Designation code: MW-EN 13162-T4.

Handling, Storage, Health and Safety	Information regarding storage, installation and handling of Isover products and health & safety information can be found at isover.co.uk/healthandsafety . Achieves a Eurofins Gold product status for indoor air quality (certificate available at isover.co.uk/Eurofins). EUCEB certified, demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008 (to download the certification, please visit isover.co.uk/accreditations).
Quality	All Isover products are manufactured under Quality Management Standard - ISO 9001.



Isover

Saint-Gobain Isover UK Limited,
Saint-Gobain House, East Leake, Loughborough,
Leicestershire, LE12 6JU.

**Customer Service -
Order Placement and Enquiries**

Tel: 0800 0322 555
Email: isover.customerservice@saint-gobain.com

Technical Support Team

Email: isover.technical@saint-gobain.com

isover.co.uk

Published date: 25 November 2024

Isover reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at isover.co.uk

Saint-Gobain Isover UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.