

Product Data Sheet
Application: External Walls

# TIMBER FRAME ROLL 40



### **Thermal Insulation for Timber Frame Walls**

Timber Frame Roll 40 is a glass mineral wool roll providing thermal performance and acoustic benefits in timber frame walls. The resilient and flexible rolls can be friction fitted between standard timber studs, ensuring straightforward installation and helping to minimise gaps and maximise thermal performance.

## **Features and Benefits**



#### **Thermal Performance**

Thermal conductivity of 0.040 W/m.K. Helps to reduce heat loss within the building envelope and decrease energy costs.



#### **Fire Classification**

Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.



#### **Acoustic Benefits**

The fibre structure of the glass mineral wool traps sound energy and dissipates it within its thickness, helping to improve the acoustic comfort of those living or working within the building.



#### Easy to Install

Straightforward to handle, cut and install with minimal waste (off-cuts can be reused). Friction fits between timber stud centres with no need for additional fixings.



#### Sustainability

Manufactured from up to 82% recycled glass on a plant that uses 100% renewable electricity. For further details, see the Environmental section below or visit insulation-uk.com/CSR

# **Key Considerations**

When using ISOVER Timber Frame Roll 40, you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Please refer to the following product documents which are available at insulation-uk.com/products/isover-timber-frame-roll-40 (product properties) and insulation-uk.com/healthandsafety (safety properties):

- Declaration of Performance
- Safe Use Instruction Sheet

# **Product Specification**

Product code	Thickness (mm)	Length (m)	Width (m)	Roll area (m²)	Rolls per pallet	Pallet area (m²)	λD Declared thermal conductivity (W/m.K)	RD Declared thermal resistance (m².K/W)
5200625582	90	10.13	2 x 0.57	11.55	24	277.16	0.040	2.25
5200625572	140	6.50	2 x 0.57	7.41	24	177.84	0.040	3.50

## **Characteristics**

Thermal	Declared thermal conductivity of 0.040 W/m.K under EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.	Handling, Storage, Health and Safety	Information regarding storage, installation and handling of ISOVER products and health & safety information can be found at insulation-uk.com/healthandsafety.  Achieves a Eurofins Gold product status for indoor air quality (certificate available at insulation-uk.com/Eurofins).  EUCEB certified, demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008 (to download the certification, please visit insulation-uk.com/accreditations).		
Fire	Euroclass A1 Reaction to Fire classification according to EN 13501-1.				
Environmental	All Isover products are manufactured under Environmental Management System - ISO 14001:2015.				
Recycled Content	Manufactured from up to 82% recycled glass.	Quality	All ISOVER products are manufactured under Quality Management Standard - ISO 9001.		
Certification	UKCA Marked to BS EN 13162. CE marked to EN 13162. Designation code: MW-EN 13162-T1.				



#### **ISOVER**

White House Industrial Estate, Runcorn, Cheshire, WA7 3DP

#### Customer Service -Order Placement and Enquiries

Tel: 01473 820820 Email: iukcustomerservice@saint-gobain.com

#### **Technical Support Team**

Email: isovertechnical@saint-gobain.com

insulation-uk.com

Published date: 29 Feb 202/

ISOVER reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at insulation-uk.com  $\,$ 

Saint-Gobain ISOVER UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.